



DMR Handheld Radios



BR200D UHF / VHF
BR300D UHF / VHF

WORKS WITH YOUR CURRENT DMR RADIOS!

Cost-Effective DMR Digital Portable Two-Way Radio

Compact, versatile and cost-effective, the BR300D Series of radios is completely compatible with any other DMR Digital radio on the market. It operates in both digital and analog modes, delivering clear and loud communication. BR300D comes with a display and full keypad and with its versatility it can be used in a wide range of applications. Industries such as K12 Education, Colleges and Universities, Manufacturing, Security, Hotels and more. When safety and reliability is critical, the BR200D/BR300D Series of radios is the best choice for your communication needs.

BR200D / BR300D FEATURES

Exceptional Audio Quality – The BR200D/BR300D radios completely eliminate background noise and static from voice transmissions, delivering a crystal clear message compared to analog radios.

Analog + Digital Operation – Capable to operate in both analog and digital modes the BR200D/BR300D radios give you the option to upgrade to digital at your own pace.

Smallest Digital Radio on the Market – Compact, lightweight design, making the BR200/BR300D very comfortable and easy to use through a long work shift.

Power is Performance – The BR200/BR300D radios are designed to conserve battery power reducing the power consumption by 40% compared to analog radios. This extends the radios operating time, enabling your employees to stay connected for up to 13 hours of regular usage. Eliminating the need to recharge during long shifts.

Emergency and Security – In critical situations, the radio user can initiate an emergency alarm which overrides all activity on the channel.

Private and Group Call – Allows users to talk privately with specific individuals or groups without broadcasting to everyone on the channel.

Signaling – 2-Tone, 5-Tone, DTMF Encode/Decode and MDC1200 Encode: PTT ID (identifies outbound calls), Individual/Group Call (receive/place calls from specific individuals or groups), Call Alert (tone indicates new inbound call), and Alarm (sounds alarm or notifies system administrator of emergency).

Radio Stun/Kill/Revive – Allows the radio administrator to disable radio if it is lost or stolen.

Voice Annunciation – Announces channel number when channel is changed.

Industry Leading Warranty – Backed by a Three (3) Year Warranty.



- ① **2 Programmable Side Buttons** Place your favorite features at your fingertips.
- ② **6" Antenna** Provides best radio coverage.
- ③ **32 / 1,000 Channels** Plenty of choices for specific assignments.
- ④ **Programmable Top Emergency Button** Activates emergency signal or can be programmed to make it easy to use your favorite feature.
- ⑤ **On/Off and Analog/Digital Audio** Clear, crisp audio that's 50% louder than Motorola's HT750.
- ⑥ **Two Prong Right Angle Connector** Compatible with Motorola CP200/CP200d accessories.
- ⑦ **Keypad/Menu Keys** 12 alpha/numeric/3 menu keys. (BR300D only).



BR200D / BR300D SPECIFICATIONS

GENERAL			
Frequency Bands	136 - 174 MHz (VHF "V"); 400 - 470 MHz (UHF "U"); 450 - 520 MHz (UHF "U2")		
Dimensions	4.5" x 1.3" x 2.1" / 113mm x 54mm x 33.5mm		
Weight	9.5 ounces (270g) with 1700 mAh battery		
Battery	Li-ion 1700 mAh. Optional 2000 mAh		
Battery Life	Approx. 10 hours, high transmit power 1700 mAh battery, 90:5:5 duty cycle		
Channels	32 (BR200D) / 1,000 (BR300D)		
Frequency Stability	± 0.5 ppm (typical)		
Display	102 x 64 pixels (BR300D only)		
Switching Bandwidth	Full band		
Modulation	Pre-emphasized FM, C4FM		
Environmental Protection	IP65 (Water Resistant/Dust Proof)		
Environmental Standards	MIL-STD-810 F	Method	Procedure
	Low Pressure (Altitude), Storage	500.4	I
	Low Pressure (Altitude), Operational	500.4	II
	High Temp, Storage	501.4	I
	High Temp, Operating	501.4	II
	Low Temp, Storage	502.4	I
	Low Temp, Operating	502.4	II
	Thermal Shock	503.4	I
	Solar Radiation	505.4	I(A2)
	Relative Humidity	507.4	
	Dust	510.4	I
	Sand	510.4	II
	General Vibration: Truck/trailer/tracked - restrained cargo	514.5	I Cat 24
	General Vibration: Minimum Integrity	514.5	I Cat 24
	Shock - Transit Drop	516.5	IV
Operating Temperature	-22°F (-30°C) - 140°F (60°C)		

TRANSMITTER SPECIFICATION	
Power Output	0.5 - 5 W, 3 programmable levels
Audio Distortion	<3% at 1 kHz, 60% deviation
Channel Spacing	12.5KHz
Conducted, Radiated Spurious Emission	-36dBm@<1GHz, -30dBm@>1GHz
Adjacent Channel Power	-60dB@12.5KHz
Audio Response	+1 dB to -3 dB
FM Modulation Mode	12.5KHz : 11KOF3E
4FSK Digital Mode	12.5KHz (data only): 7K60FXD 12.5KHz (data+ voice): 7K60FXE
Modulation Maximum Deviation	2.5KHz@12.5KHz
Audio Distortion	3% (Type)
Digital Protocol	ETSI TS 102 361-1, -2, -3
Vocoder Type	AMBE3000™
Hum and Noise	>40 dB (12.5 kHz)
RECEIVER SPECIFICATION	
Analog Sensitivity	0.35uV/-116dBm(20 dB SINAD) 0.22uV/-120dBm(Type)
Digital Sensitivity	0.3uV/-117.4dBm (BER 5%) 0.7uV/-110dBm (BER 1%)
Adjacent Channel Selectivity	TIA603C: 65dB@12.5KHz ETSI: 60dB@12.5KHz
Spurious Response Rejection	TIA603C : 75dB ETSI : 70dB
Conducted Spurious Emission	- 57dBm@ < 1 GHz , - 47dBm @> 1GHz
Audio Output	1W
Blocking	>95 dB at +/- 1 MHz



For more information, visit www.RCACommunicationsSystems.com

ACCESSORIES & OPTIONS



**Light Duty
Speaker Mic**
SM220-X03



**Heavy Duty
Speaker Mic**
SM310-X03



**Light Duty Behind
the Head Headset**
HS11V-X03



Nylon & Leather Holsters
HN200FC/SC/FL/SL
HN300FC/SC/FL/SL
HL200FC/SC/FL/SL
HL300FC/SC/FL/SL



**One-Wire
Surveillance Kit
In-Ear Style**
SK11NE-X03



**Two-Wire
Surveillance Kit
In-Ear Style**
SK21NE-X03



**High Noise Headset - Over
the Head & Behind the Head**
HS61NR-X03, HS71NR-X03



3" & 6" Antennas
ANH200U/V-3
ANH200U/V-6



**1700mAh Lithium-Ion
Battery**
B2017LI



**2000mAh Lithium-Ion
Battery**
B2020LI



Single Unit Charger
CH2001 PKG



**Multi-Unit
Rapid-Rate Charger**
CHU6 PKG



For more information, visit
www.RCACommunicationsSystems.com

© 2016 RCA Communications Systems. All rights reserved.
Specifications subject to change.

Authorized North American Distributor:

Discount Two-Way Radio
555 W. Victoria St., Rancho Dominguez, CA 90220
Toll Free: (800) 895-5122 | Fax: (877) 291-9565
info@dtwr.com
www.DiscountTwo-WayRadio.com

BR200D/BR300DBroch - Ver. 20160913